IN THE SPECIFICATION:

At page 1, line 4, after "This application" insert --is a continuation application of Application Serial No. 08/067,783, entitled "VIDEOPHONE SYSTEM FOR SCRUTINY MONITORING WITH COMPUTER CONTROL," filed on May 25, 1993, now abandoned, which--

A1 B

At page 10, line 32, replace "touch tone" with --TOUCH TONE® (DTMF pad entry)--.

At page 23, line 25, after "and "#"" insert --for generating DTMF signals in accordance with standard convention--.

A2

IN THE DRAWINGS:

Please amend Figure 3 as follows:

--Within the block in broken lines designated as L_1 (for a remote scrutiny location), insert an additional block in solid lines with a caption "VCR" and connect it to the interface unit block designated as 28 with a line, and insert reference numeral 35 at the end of a leading line to designate the new block.--

IN THE CLAIMS:

Please cancel claim 1, without prejudice, and add the following new claims 26-51:

A3 cont

--26. A system for communicating with a plurality of remote locations from a central station utilizing dial-up telephone facilities comprising:

television communication structures at said plurality of remote locations for telephonically providing representative image television signals and for telephonically receiving and sending audio signals to carry voice;

a plurality of television display structures, including speaker phones, at said central station for receiving telephonic signals and displaying said scene representative television signals;

telephonic interface apparatus for interconnecting said television camera structures at said remote locations with said television display structures at said central location and including at least one audio response unit at said central station; and

a control unit for controlling said telephonic interface apparatus to establish television and audio communication between a television camera structure at one of said remote locations and one of said television display structures at said central station, with said central station receiving a remote location display and said remote station receiving prompts from said audio response unit for manually actuating a keypad to provide DTMF signals.--

--27. A system according to claim 26 further including means for controlling said television display structures in accordance with said DTMF signals.--

--28. A system according to claim 26 wherein said control unit includes means for establishing television communication in response to DTMF signals representing a personal identification number.--

--29. A system according to claim 26 wherein said telephonic interface apparatus includes means for providing "D" channel type signals and wherein said control unit establishes communication to a select television display structure in accordance with said "D" channel type signals.--

A3 cont'

--30. A system for communicating with a plurality of remote locations from at least one central station utilizing dial-up telephone facilities, comprising:

television camera structures positioned at said remote locations for providing scene representative television signals and including speaker phones and keypads;

at least one television display structure including speaker phones at said central station for receiving telephonic signals and displaying said scene representative signals;

telephone interface apparatus for selectively interconnecting said television camera structures and said television display structure and including at least one audio response unit at said central station; and

a control unit at said central station for controlling said telephone interface unit to provide voice prompts by said audio response unit for manual activation of a keypad to provide DTMF signals.--

--31. A system according to claim 30 wherein said control unit controls said television display device in accordance with said DTMF signals.--

--32. A system according to claim 31 wherein said control unit provides graphic signals to supplement said scene representative signals in response to said DTMF signals.--

A3 cont.

--33. A system according to claim 30 further including a printer coupled to said control unit.--

--34. A system for monitoring a plurality of scrutiny locations from a central station using dial-up telephone facilities comprising:

television camera structures at said plurality of scrutiny locations for providing representative dynamic image television signals representative of scenes;

at least one television display structure at said central station;

telephonic interface apparatus for interconnecting said television structures at said scrutiny locations to said central location; and

a control unit at said central station including memory for storing scrutiny location call data and graphic display data, said control unit for actuating said telephonic interface apparatus to establish television communication between said central station and said scrutiny locations to provide a sequence of remote location displays at said central station showing a scene and graphic display data, said control unit further including interrupt structure for receiving an interrupt signal manifesting a predetermined circumstance to interrupt said sequence and to provide an alternate display of a scene from one of said scrutiny locations along with graphic display data.--

A3 cont.

--35. A system according to claim 34 further including sensor units at said scrutiny locations for providing said interrupt signal to said control unit.--

--36. A system according to claim 34 wherein said control unit includes means for providing graphic displays on said remote location displays.--

--37. A system according to claim 34 further including operator control structure at said central station to provide said interrupt signal.--

--38. A system according to claim 34 wherein said television camera structures for at least one of said plurality of security locations includes a processor for interfacing said control unit at said central station to control said television communication between said central station and said one scrutiny location.--

--39. A system according to claim 38 wherein said television camera structure for said one scrutiny location includes a plurality of sensor units at said scrutiny locations for providing interrupt signals to said control unit.--

--40. A system for observing a plurality of monitored locations from a central station utilizing dial-up telephone facilities comprising:

at least one television camera structure at each of said plurality of monitored locations for providing scene representative dynamic image television signals for location displays;

a plurality of switch structures at each of said plurality of monitored locations for providing alert signals indicating various alert situations;

at least one television display structure at said central station for providing a scene represented by said dynamic image television signals;

telephonic interface apparatus for interconnecting said television camera structures at said monitored locations and said central station, said telephonic interface apparatus including at least one autodialer apparatus at said monitored locations for dial-up connection originated from a monitored location, said telephonic apparatus further including "D" channel type apparatus, for providing "D" channel type signals to manifest said alert situations; and

a control computer activated by said "D" channel type signals and including memory structure addressable to supply location graphic data, including an alert situation indication for actuating said television display structure to display the graphic data including an alert situation indication along with said scene.--

--41. A system according to claim 40 wherein said memory structure is addressed by a monitored location telephone number as indicated by ANI signals to provide graphic data relating to identification.--

--42. A system according to claim 40 wherein said memory structure is addressed by "D" channel type signals in the form of DNIS signals.--

--43. A system according to claim 40 wherein said location graphic data further includes identification data relating to a monitored location.--

--44. A system according to claim 40 including a plurality of television display structures at said central station and wherein said control computer couples a specific one of said television display structures for interconnection to a select television display structure under control of said "D" channel type signals.--

BOARD DECISION

A3 cont.

--45. A system according to claim 40 further including a billing data memory section for storing billing time as related to said monitored locations.--

A3

--46. A system for communicating with a plurality of remote locations from a central station utilizing dial-up telephone facilities comprising:

television communication structures at said plurality of remote locations for telephonically providing representative image television signals and for telephonically receiving and sending audio signals to carry voice;

a plurality of television display structures at said central station for providing a display from said

representative image television signals for providing and manifesting audio signals;

telephonic interface apparatus for interconnecting said television communication structures at said remote locations and said central station to provide two-way audio and at least one-way video communications;

a memory unit for storing time sequence data and remote location data on said remote locations; and

a control computer coupled to said memory apparatus and said telephonic interface apparatus for actuating said telephonic interface apparatus to selectively communicate from said remote location to one of said television display structures in accordance with said time sequence data and to control the display of said television display structures.--

--47. A system according to claim 46 wherein said remote location data includes identification data relating to said remote locations.--

--48. A system according to claim 46 wherein said control computer couples a specific one of said television display structures for interconnection to a select television display structure under control of "D" channel type signals provided by said telephonic interface apparatus.--